

## Passive Video Balun AHD/ CVI/ TVI/ CBVS UTP 101HD

### Features:

- Compatible with all: HDCVI, HDTV, AHD, CBVS
- Up to 450m for 720P CVI Cameras.
- Up to 250m for 1080P CVI Cameras.
- Up to 250m for 720P/1080P TVI Cameras.
- Up to 320m for 720P AHD Cameras.
- Up to 250m for 1080P AHD Cameras.
- Up to 500m for CBVS Cameras.
- No power required.
- 60dB cross talk and noise immunity.
- Built-in transient suppression protection.
- Innovative combinable design.



### Technical Specifications:

Frequency response: DC to 60Mhz.  
Attenuation: 0.5dB Type.  
CMRR: 60dB.  
Surge Protection: 4KV / ESD: 8KV  
Connectors: Male BNC and "Press-Fit" terminal blocks.  
Impedance: BNC: 75 ohms / Terminal: 100 ohms.  
Working Temperature: -10°C to +70°C.  
Storage Temperature: -30°C to +70°C.  
Humidity: 0 to 95%.  
Dimension: 39 x 17 x 19mm (excluding connectors).  
Material: ABS Plastic  
Body color: Black  
Net Weight: 50g

Data subject to change without prior notice.  
Some products may not be available in all countries.